

## 50/15 PRIME M IOT

**Cod. PR-OF200-040-M**



Oil free air compressor IOT version, 2-cylinder, with an air output of 152 l/min at 5 bar pressure. Tank capacity 40 L, internal surface treatment to protect against corrosion.

Equipped with a membrane dryer and a series of sensors that detect all operating parameters and any faults in real time. All models also have a touchscreen display and are ready for connection to the MGF Cloud.

MGF offers each compressor in the IOT range in 3 versions:

Eco - configuration with code STDYB

High - configuration with code STDYH

Full - configuration with code STDYF

Cod.	Air Dryer	FAD Fad @ 5bar	Motor	Voltage Hz	Receiver	Noise Level	Duty Cycle	max P.	Size	net Weight
50/15 PRIME M IOT PR-OF200-040-M	Yes	m <sup>3</sup> /min l/min 0.152 152	-	230V 50Hz	l 40	db(A) 66	70 %	bar 8	mm 710X410X770	Kg 50
50/15 PRIME M IOT 400 V PR-OF200-040-M-400	Yes	m <sup>3</sup> /min l/min 0.152 152	kW 1.5	400V 50/60Hz	l 40	db(A) 66	70 %	bar 8	mm 710X410X770	Kg 50

### Air delivery performance

