

100/30 TANDEM PRIME M IOT

Cod. PR-OF400-090-MT



Oil free air compressor IOT version, 4 cylinders, with an air output of 305 l/min at 5 bar pressure. Tank capacity 90 L, internal surface treatment to protect against corrosion.










Equipped with a membrane dryer and a series of sensors that detect all operating parameters and any faults in real time. All models also have a touchscreen display and are ready for connection to the MGF Cloud.

MGF offers each compressor in the IOT range in 3 versions:

Eco - configuration with code STDYB

High - configuration with code STDYH

Full - configuration with code STDYF

Cod.	Air Dryer	FAD  F _{ad} @ 5bar	Motor 	Voltage  Hz	Receiver 	Noise Level 	Duty Cycle 	max P. 	Size 	net Weight 
100/30 TANDEM PRIME M IOT PR-OF400-090-MT	Yes	m ³ /min 0.305 l/min 305	kW 3	230V 50Hz	l 90	db(A) 69	70 %	bar 8	mm 110x600x810	Kg 102
100/30 TANDEM PRIME M IOT 400 V PR-OF400-090-MT-400	Yes	m ³ /min 0.305 l/min 305	kW 3	400V 50/60Hz	l 90	db(A) 69	70 %	bar 8	mm 1100x600x810	Kg 102

Air delivery performance

