

CS 30/15 PRIME S IOT

Cod. PR-CS200-040



Oil free air compressor IOT version, 2-cylinder, with an air output of 170 l/min at 5 bar pressure. Tank capacity 40 L, internal surface treatment to protect against corrosion.










Equipped with a soundproof cabin and a series of sensors that detect all operating parameters and any faults in real time. All models are also equipped with a touchscreen display and are ready for connection to the MGF Cloud.

MGF offers each compressor in the IOT range in 3 versions:

Eco - configuration with code STDYB

High - configuration with code STDYH

Full - configuration with code STDYF

Cod.	Air Dryer	FAD  F _{ad} @ 5bar	Motor 	Voltage  Hz	Receiver 	Noise Level 	Duty Cycle 	max P. 	Size 	net Weight 
CS 30/15 PRIME S IOT PR-CS200-040	No	m ³ /min 0.17 l/min 170	kW 1.5	230V 50Hz	l 40	db(A) 53	70 %	bar 8	mm 720x490x890	Kg 94
CS 30/15 PRIME S IOT 400 V PR-CS200-040-400	No	m ³ /min 0.17 l/min 170	kW 1.5	400V 50/60Hz	l 40	db(A) 53	70 %	bar 8	mm 720x490x890	Kg 94

Air delivery performance

