

CS 100/30 TANDEM PRIME M IOT

Cod. PR-CS400-090-MT



Oil free air compressor IOT version, 4 cylinders, with an air output of 340 l/min at 5 bar pressure. Tank capacity 90 L, internal surface treatment to protect against corrosion.

Equipped with a membrane dryer, soundproof cabin and a series of sensors that detect all operating parameters and any faults in real time. All models also have a touchscreen display and are ready for connection to the MGF Cloud.

MGF offers each compressor in the IOT range in 3 versions:

Eco - configuration with code STDYB

High - configuration with code STDYH

Full - configuration with code STDYF

Cod.	Air Dryer	FAD F _{ad} @ 5bar	Motor	Voltage Hz	Receiver	Noise Level	Duty Cycle	max P.	Size	net Weight
CS 100/30 TANDEM PRIME M IOT PR-CS400-090-MT	Yes	m ³ /min l/min 0.34 340	kW 3	230V 50Hz	l 90	db(A) 56	70 %	bar 8	mm 1245x725x1020	Kg 215
CS 100/30 TANDEM PRIME M IOT 400V PR-CS400-090-MT3	Yes	m ³ /min l/min 0.34 340	kW 3	400V 50/60Hz	l 90	db(A) 56	70 %	bar 8	mm 1245x725x1020	Kg 215

Air delivery performance

