



MGF HYBRID A5

Cod. AS-150-EX-400-AS








Semi-dry 2 Hp suction pump, maximum flow rate 2,500 l / min, underpressure 180 mbar. Three-phase version motor. The high reliability of the centrifugal separation system guarantees the correct operation of the suction pump for several years. The pump impellers are made of aluminum and guarantee maximum reliability over time. Version with amalgam separator (code AS-150-EX-AS).



Maximum simultaneous use: 4



Dental Chairs: 6

							
Air capacity		Motor	Voltage Hz	Noise Level	Duty Cycle	max Oper. Head	Size
m ³ /min	l/min	kW		db(A)		mbar	mm
0.0025	2.5	1.5	400V 50/60Hz	65	100 %	180	620x915x455
							kg
							35

Air delivery performance



Maintenance kits

Kit.	Description	Type	Hours
AS-50060241	Annual maintenance kit for HYBRID 5	Ordinary	1y
	<p>The annual maintenance kit for HYBRID 5 includes:</p> <ul style="list-style-type: none"> • Filter screen, 1 unit • Water collector, 1 unit • 1.2 m of PVC pipe for water separator • Plug-in angle adapter for the pressure sensor connection tube, 1 unit • tube (green), 1 unit • information Sheet 		

Kit.	Description	Type	Hours
AS-50060210	Hybrid 1,2,5 extraordinary maintenance kit The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Extraordinary	4.000h/4y