



HYBRID A1S

Cod. AS-075-EX1-AS








Semi-wet 0.75 Hp suction pump, maximum flow rate 1.100 l /min, underpressure 120 mbar. The high reliability of the centrifugal separation system guarantees correct operation of the suction pump for several years. The pump impellers are made of aluminum and guarantee maximum reliability over time. Version with amalgam separator.



Maximum simultaneous use: 1



Dental Chairs: 2

 Air capacity	 Motor	 Voltage Hz	 Noise Level	 Duty Cycle	max Oper. Head	 Size	 net Weight	
m³/min 0.0011	l/min 1.1	kW 0.55	230V 50Hz	db(A) 63	100 %	mbar 120/140	mm 720x320x350	Kg 15

Maintenance kits

Kit.	Description	Type	Hours
AS-50060240	HYBRID 1, HYBRID 2 annual maintenance kit includes: <ul style="list-style-type: none"> • Water collector - AS-50060214, 1 quantity • Non-return valve, water separator - AS-50060220, 1 quantity • 1.2 m of PVC pipe for water separation • Information Sheet 	Ordinary	1y
AS-50060210	Hybrid 1,2,5 extraordinary maintenance kit The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Ordinary	4.000h/4y