










## MGF HYBRID 5

**Cod. AS-150-EX**

Semi-dry 2 Hp suction pump, maximum flow rate 2,500 l / min, maximum head 180 mbar. The high reliability of the centrifugal separation system guarantees the correct operation of the suction pump for several years. The pump impellers are made of aluminum and guarantee maximum reliability over time. The HYBRID 5 model is also available in the version with amalgam separator (code AS-150-EX-AS).

 Maximum simultaneous use: 4

 Dental Chairs: 6

					<b>max Oper. Head</b>		
<b>Air capacity</b>	<b>Motor</b>	<b>Voltage Hz</b>	<b>Noise Level</b>	<b>Duty Cycle</b>		<b>Size</b>	<b>net Weight</b>
m <sup>3</sup> /min 0.0025	l/min 2.5	kW 1.5	230V 50Hz	db(A) 65	100 %	mbar 180	mm 620x460x455
							Kg 30

## Maintenance kits

<b>Kit.</b>	<b>Description</b>	<b>Type</b>	<b>Hours</b>
AS-50060241	<b>Annual maintenance kit for HYBRID 5</b> The annual maintenance kit for HYBRID 5 includes: <ul style="list-style-type: none"> <li>• Filter screen, 1 unit</li> <li>• Water collector, 1 unit</li> <li>• 1.2 m of PVC pipe for water separator</li> <li>• Plug-in angle adapter for the pressure sensor connection tube, 1 unit</li> <li>• tube (green), 1 unit</li> <li>• information Sheet</li> </ul>	Ordinary	1y
AS-50060210	<b>Hybrid 1,2,5 extraordinary maintenance kit</b> The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Extraordinary	4.000h/4y