



MGF HYBRID A5

Cod. AS-150-EX-AS

Semi-dry 2 Hp suction pump, maximum flow rate 2,500 l / min, underpressure 180 mbar. The high reliability of the centrifugal separation system guarantees the correct operation of the suction pump for several years. The pump impellers are made of aluminum and guarantee maximum reliability over time. Version with amalgam separator (code AS-150-EX-AS).

 Maximum simultaneous use: 4

 Dental Chairs: 6

Air capacity		Motor	Voltage Hz	Noise Level	Duty Cycle	max Oper. Head	Size	net Weight
m ³ /min 0.0025	l/min 2.5	kW 1.5	230V 50Hz	db(A) 65	100 %	mbar 180	mm 620x915x455	Kg 35

Maintenance kits

Kit.	Description	Type	Hours
AS-50060241	<p>Annual maintenance kit for HYBRID 5</p> <p>The annual maintenance kit for HYBRID 5 includes:</p> <ul style="list-style-type: none"> • Filter screen, 1 unit • Water collector, 1 unit • 1.2 m of PVC pipe for water separator • Plug-in angle adapter for the pressure sensor connection tube, 1 unit • tube (green), 1 unit • information Sheet 	Ordinary	1y
AS-50060210	<p>Hybrid 1,2,5 extraordinary maintenance kit</p> <p>The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.</p>	Extraordinary	4.000h/4y