













MGF HYBRID 1

Cod. AS-094-EX

Semi-dry 1.2 Hp suction pump, maximum flow rate 1.100 l/min, maximum head 180 mbar. The high reliability of the centrifugal separation system guarantees correct operation of the suction pump for several years without the need for intervention. The pump impellers are made of aluminum and guarantee maximum reliability over time. The HYBRID 1 model is also available in the version with amalgam separator (code AS-094-EX-AS).

-  Maximum simultaneous use: 2
-  Dental Chairs: 2

								
Air capacity	Motor	Voltage Hz	Noise Level	Duty Cycle	max Oper. Head	Size	net Weight	
m³/min 0.0011	l/min 1.1	kW 0.94	230V 50Hz	db(A) 57	100 %	mbar 180	mm 570x422x400	Kg 22

Maintenance kits

Kit.	Description	Type	Hours
AS-50060240	HYBRID 1, HYBRID 2 annual maintenance kit includes: <ul style="list-style-type: none"> • Water collector - AS-50060214, 1 quantity • Non-return valve, water separator - AS-50060220, 1 quantity • 1.2 m of PVC pipe for water separation • Information Sheet 	Ordinary	1y
AS-50060210	Hybrid 1,2,5 extraordinary maintenance kit The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Extraordinary	4.000h/4y