










MGF HYBRID A2 400V

Cod. AS-100-EX-400-AS

Semi-dry suction pump of 1,5 Hp, maximum flow rate 1,500 l / min, underpressure 180 mbar. The high reliability of the centrifugal separation system guarantees the correct operation of the suction pump for several years. The pump impellers are made of aluminum and guarantee maximum reliability over time.

 Maximum simultaneous use: 3

 Dental Chairs: 3

					max Oper. Head		
Air capacity	Motor	Voltage Hz	Noise Level	Duty Cycle		Size	net Weight
m ³ /min 0.0015	l/min 1.5	kW 111.3	400V 50/60Hz	db(A) 63	100 %	mbar 180	mm 645x780x400
							Kg 29.5

Maintenance kits

Kit.	Description	Type	Hours
AS-50060240	HYBRID 1, HYBRID 2 annual maintenance kit includes: <ul style="list-style-type: none"> • Water collector - AS-50060214, 1 quantity • Non-return valve, water separator - AS-50060220, 1 quantity • 1.2 m of PVC pipe for water separation • Information Sheet 	Ordinary	1y
AS-50060210	Hybrid 1,2,5 extraordinary maintenance kit The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Extraordinary	4.000h/4y