











## MGF HYBRID 5 400V

**Cod. AS-150-EX-400**

Semi-dry 2 Hp suction pump, maximum flow rate 2,500 l/min, maximum head 180 mbar. Three-phase version motor. The high reliability of the centrifugal separation system guarantees correct operation of the suction pump for several years without the need for intervention. Maximum absorption 4.3-4.4 Amp. The pump impellers are made of aluminum and guarantee maximum reliability over time. The HYBRID 5 model is also available in the version with amalgam separator (code AS-150-EX-400-AS).

 Maximum simultaneous use: 4

 Dental Chairs: 6

								
Air capacity	Motor	Voltage Hz	Noise Level	Duty Cycle	max Oper. Head	Size	net Weight	
m³/min 0.0025	l/min 2.5	kW 2	400V 50/60Hz	db(A) 65	100 %	mbar 180	mm 620x460x455	Kg 30

## Maintenance kits

Kit.	Description	Type	Hours
AS-50060241	<b>Annual maintenance kit for HYBRID 5</b> The annual maintenance kit for HYBRID 5 includes: <ul style="list-style-type: none"> <li>• Filter screen, 1 unit</li> <li>• Water collector, 1 unit</li> <li>• 1.2 m of PVC pipe for water separator</li> <li>• Plug-in angle adapter for the pressure sensor connection tube, 1 unit</li> <li>• tube (green), 1 unit</li> <li>• information Sheet</li> </ul>	Ordinary	1y
AS-50060210	<b>Hybrid 1,2,5 extraordinary maintenance kit</b> The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Extraordinary	4.000h/4y