

## 50/25 PRIME S IOT

**Cod. PR-OF300-040**



IOT version oil free air compressor, 3 cylinders, with a compressed air flow rate of 250 l/min at 5 bar pressure. Tank capacity 40 L, treatment of the internal surface to protect against corrosion.










Equipped with a series of sensors that detect all the operating parameters and any anomalies in real time. All models are also equipped with a touchscreen display and are set up for connection to the MGF Cloud.

MGF offers each compressor in the IOT range in 3 versions:

Echo - configuration with code STDYB

High - configuration with code STDYH

Full - configuration with code STDYF

Cod.	Air Dryer	FAD  Fad @ 5bar	Motor 	Voltage  Hz	Receiver 	Noise  Level	Duty  Cycle	max  P.	Size 	net  Weight
50/25 PRIME S IOT PR-OF300-040	No	m <sup>3</sup> /min l/min 0.25 250	kW 2.2	230V 50Hz	-	db(A) 66	70 %	bar 8	mm 600x410x810	Kg 54
50/25 PRIME S IOT 400 V PR-OF300-040-400	No	m <sup>3</sup> /min l/min 0.25 250	kW 2.2	400V 50/60Hz	l 40	db(A) 66	70 %	bar 8	mm 600x410x810	Kg 54

## Air delivery performance

