

## CS 100/50 TANDEM PRIME S IOT

**Cod. PR-CS600-090-T**



Oil free air compressor IOT version, 6 cylinders, with an air output of 500 l/min at 5 bar pressure. Tank capacity 90 L, internal surface treatment to protect against corrosion.

Equipped with a soundproof cabin and a series of sensors that detect all operating parameters and any anomalies in real time. All models are also equipped with a touchscreen display and are ready for connection to the MGF Cloud.

MGF offers each compressor in the IOT range in 3 versions:

Eco - configuration with code STDYB

High - configuration with code STDYH

Full - configuration with code STDYF

Cod.	Air Dryer	FAD F <sub>ad</sub> @ 5bar	Motor	Voltage Hz	Receiver	Noise Level	Duty Cycle	max P.	Size	net Weight
CS 100/50 TANDEM PRIME S IOT PR-CS600-090-T	No	m <sup>3</sup> /min l/min 0.5 500	kW 4.4	230V 50Hz	l 90	db(A) 56	70 %	bar 8	mm 1245X725X1020	Kg 225
CS 100/50 TANDEM PRIME S IOT 400 V PR-CS600-090-T3	No	m <sup>3</sup> /min l/min 0.5 500	kW 4.4	400V 50/60Hz	l 90	db(A) 56	70 %	bar 8	mm 1245X725X1020	Kg 225

### Air delivery performance

