

50/25 PRIME M IOT

Cod. PR-OF300-040-M



Oil free air compressor IOT version, 3 cylinders, with compressed air output of 225 l/min at 5 bar pressure. Tank capacity 40 L, internal surface treatment to protect against corrosion.

Equipped with membrane dryer and a series of sensors that detect all operating parameters and any anomalies in real time. All models are also equipped with a touchscreen display and are prepared for connection to the MGF Cloud.

MGF offers each compressor in the IOT range in 3 versions:

Eco - configuration with STDYB code

High - configuration with code STDYH

Full - configuration with code STDYF

Cod.	Air Dryer	FAD Fad @ 5bar	Motor	Voltage Hz	Receiver	Noise Level	Duty Cycle	max P.	Size	net Weight
50/25 PRIME M IOT PR-OF300-040-M	Yes	m ³ /min l/min 0.225 225	kW 2.2	230V 50Hz	l 40	db(A) 66	70 %	bar 8	mm 710x410x810	Kg 58
50/25 PRIME M IOT 400 V PR-OF300-040-M-400	Yes	m ³ /min l/min 0.225 225	kW 2.2	400V 50/60Hz	l 40	db(A) 58	70 %	bar 8	mm 710x410x810	Kg 66

Air delivery performance

