

100/50 TANDEM PRIME S IOT

Cod. PR-OF600-090-T



Oil free air compressor IOT version, 6 cylinders, with an air output of 500 l/min at 5 bar pressure. Tank capacity 90 L, internal surface treatment to protect against corrosion.

Equipped with a series of sensors that detect all operating parameters and any faults in real time. All models also have a touchscreen display and are prepared for connection to the MGF Cloud.

MGF offers each compressor in the IOT range in 3 versions:

Eco - configuration with code STDYB

High - configuration with code STDYH

Full - configuration with code STDYF

Cod.	Air Dryer	FAD F _{ad} @ 5bar	Motor	Voltage Hz	Receiver	Noise Level	Duty Cycle	max P.	Size	net Weight
100/50 TANDEM PRIME S IOT PR-OF600-090-T	No	m ³ /min l/min 0.5 500	kW 4.4	230V 50Hz	l 90	db(A) 69	70 %	bar 8	mm 1100x600x820	Kg 113
100/50 TANDEM PRIME S IOT 400 V PR-OF600-090-T3	No	m ³ /min l/min 0.5 500	kW 4.4	400V 50/60Hz	l 90	db(A) 69	70 %	bar 8	mm 1100x600x820	Kg 113

Air delivery performance

