





Solid contaminants prefilters 3 Micron

Cod. TA-PF

All filters include with automatic drain and a differential pressure gauge to indicate the saturation level of the cartridge

Cod.	 Air capacity		 max P.
Prefiltro antipolvere 3 Micron TA-PF-101 - QF	m ³ /min 0.6	l/min 600	bar 16
Prefiltro antipolvere 3 Micron TA-PF-102 - QF	m ³ /min 1	l/min 1000	bar 16
Prefiltro antipolvere 3 Micron TA-PF-103 - QF	m ³ /min 1.3	l/min 1300	bar 16
Prefiltro antipolvere 3 Micron TA-PF-104 - QF	m ³ /min 2	l/min 2000	bar 16
Prefiltro antipolvere 3 Micron TA-PF-105 - QF	m ³ /min 3.3	l/min 3300	bar 16
Prefiltro antipolvere 3 Micron TA-PF-106 - QF	m ³ /min 5.6	l/min 5600	bar 16
Prefiltro antipolvere 3 Micron TA-PF-107 - QF	m ³ /min 8.5	l/min 8500	bar 16
Prefiltro antipolvere 3 Micron TA-PF-108 - QF	m ³ /min 13	l/min 13000	bar 16
Prefiltro antipolvere 3 Micron TA-PF-109 - QF	m ³ /min 16.6	l/min 16600	bar 16
Prefiltro antipolvere 3 Micron TA-PF-110 - QF	m ³ /min 25	l/min 25000	bar 16