
















CS 100/50 TANDEM PRIME E


Cod. PR-CS600-090-T3-AN

Oil-free compressor, 6 cylinders, 350 l/min@8 bar, 90 l tank, equipped with soundproofed cabin and new generation absorption dryer capable of supplying dry air down to a dew point of -40°C.

-  Maximum simultaneous use: 6
-  Dental Chairs: 7

										
Air Dryer	Air capacity	FAD @ 8bar	Motor	Voltage Hz	Receiver	Noise Level	Duty Cycle	max P.	Size	net Weight
Yes	m³/min l/min 0.72 720	m³/min l/min 0.35 350	kW 4.4	400V 50/60Hz	l 90	db(A) 56	100 %	bar 10	mm 1245x725x1020	Kg 230

Air delivery performance



Maintenance kits

Kit.	Description	Type	Hours
TA-FL-0261-K-SCP	<p>TANDEM PRIME 2 + 2-3 + 3 M kit</p> <p>Ordinary maintenance replacement kit for TANDEM PRIME 2+2, 3+3 M versions (100/30 TANDEM PRIME M, 100/50 TANDEM PRIME M).</p> <ul style="list-style-type: none"> • 6 suction filters, code: TA-FL-058-C • 1 non-return valve pads, code: CO-PV-001 • 2 5 micron filter cartridges, code: TA-FL-001-C-SM • 2 0.01 micron filter cartridges, code: TA-FL-024-C2-SM • 4 o-rings for filters, cod. TA-FL-001-OR • 2 radiator filter cartridges, code: TA-FL-002-C • 2 0.01 micron filter cartridges, code: TA-FL-076-C • 2 AMG150 water separator cartridges, code: TA-FL-074-C • 4 o-rings for filters, cod. TA-FL-075-OR <p>Replace the filtration cartridges every 2 years.</p>	Ordinary	1.500h/2y
PR-GC-034-K-SCP	<p>TANDEM PRIME 3+3 AND PRIME 6</p> <p>Spare parts kit for extraordinary maintenance of the PRIME 3+3 & PRIME 6 versions.</p> <p>comprehends:</p> <ul style="list-style-type: none"> • 6 suction filters, code: TA-FL-058-C • 12 O-rings, code: MA-PC018 • 6 piston rings , code: MA-MG00001 • 6 piston guide rings, code: MA-MG00003 • 6 expansion rings for the segments, code: MA-MG00024 • 6 complete valve plates, code: MA-MG-02002P-C-P • 2 non-return valve pads, cod: CO-PV-001 <p>The recommended maintenance intervals for this compressor are 4000 hours/4 years.</p>	Extraordinary	4.000h/4y