








Micro OX

Cod.

Micro OX models of OX Oxygen generators.

Cod.	Inlet Pres.	Discharge press.	Ox. purity 93%	Connect. In	Connect. Out
MICRO OX-3.5 TA-GO-007	7	8	3.4	½"	½"
MICRO OX-4.5 TA-GO-008	7	5	4.3	½"	½"
MICRO OX-6 TA-GO-009	7	5	6	½"	½"
MICRO OX-9 TA-GO-010	7	5	8.6	½"	½"
MICRO OX-12 TA-GO-011	7	5	12	½"	½"
MICRO OX-18 TA-GO-012	7	5	17	½"	½"
MICRO OX-24 TA-GO-013	7	5	24	½"	½"
MICRO OX-36 TA-GO-015	7	5	36	½"	½"
MICRO OX-48 TA-GO-016	7	5	48	½"	½"

Cod.	 Motor	 Voltage Hz	 Duty Cycle	 Size	 net Weight
MICRO OX-3.5 TA-GO-007	-	230V 50Hz	100 %	mm 700x700x1700	Kg 450
MICRO OX-4.5 TA-GO-008	kW 0.3	230V 50Hz	100 %	mm 1230x1120x2200	Kg 500
MICRO OX-6 TA-GO-009	-	230V 50Hz	100 %	mm 1230x1120x2200	Kg 760

Cod.	Motor	Voltage Hz	Duty Cycle	Size	net Weight
MICRO OX-9 TA-GO-010	-	230V 50Hz	100 %	mm 1230x1120x2200	Kg 850
MICRO OX-12 TA-GO-011	-	230V 50Hz	100 %	mm 1230x1120x2200	Kg 1120
MICRO OX-18 TA-GO-012	-	230V 50Hz	100 %	mm 1600x1200x2100	Kg 1730
MICRO OX-24 TA-GO-013	-	230V 50Hz	100 %	mm 1850x1200x2200	Kg 2350
MICRO OX-36 TA-GO-015	-	230V 50Hz	100 %	mm 1600x1800x2100	Kg 3450
MICRO OX-48 TA-GO-016	-	230V 50Hz	100 %	mm 1850x2050x2200	Kg 4700

* With compressed air temperature entering the generator = 30 ° C