













MGF HYBRID 2

Cod. AS-100-EX

Pompa di aspirazione semi-secco da 1,5 Hp, portata massima 1.500 l/min , prevalenza massima 180 mbar. L'elevata affidabilità del sistema di separazione centrifugo garantisce il corretto il funzionamento della pompa di aspirazione per diversi anni. Le giranti della pompa sono realizzate in alluminio e garantiscono la massima affidabilità nel tempo. Il modello HYBRID 2 è anche disponibile nella versione con separatore di amalgama (codice AS-100-EX-AS).

-  Maximum simultaneous use: 3
-  Dental Chairs: 3

								
Air capacity	Motor	Voltage Hz	Noise Level	Duty Cycle	max Oper. Head	Size	net Weight	
m³/min 0.0015	l/min 1.5	kW 1.3	230V 50Hz	db(A) 63	100 %	mbar 180	mm 580x450x400	Kg 27

Maintenance kits

Kit.	Description	Type	Hours
AS-50060240	HYBRID 1, HYBRID 2 annual maintenance kit Comprehends: <ul style="list-style-type: none"> • Water collector - AS-50060214, 1 quantity • Non-return valve, water separator - AS-50060220, 1 quantity • 1.2 m of PVC pipe for water separation • Information Sheet 	Ordinary	1y
AS-50060210	Kit manutenzione straordinaria Hybrid 1,2,5 The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Extraordinary	4.000h/4y