



MGF HYBRID 5

Cod. AS-150-EX









Semi-dry 2 Hp suction pump, maximum flow rate 2,500 l / min, maximum head 180 mbar. The high reliability of the centrifugal separation system guarantees the correct operation of the suction pump for several years. The pump impellers are made of aluminum and guarantee maximum reliability over time. The HYBRID 5 model is also available in the version with amalgam separator (code AS-150-EX-AS).



Maximum simultaneous use: 4



Dental Chairs: 6

								
Air capacity	Motor	Voltage Hz	Noise Level	Duty Cycle	max Oper. Head	Size	net Weight	
m³/min 0.0025	l/min 2.5	kW 1.5	230V 50Hz	db(A) 65	100 %	mbar 180	mm 620x460x455	Kg 30

Maintenance kits

Kit.	Description	Type	Hours
AS-50060241	Annual maintenance kit for HYBRID 5 The annual maintenance kit for HYBRID 5 includes: <ul style="list-style-type: none"> • Filter screen, 1 unit • Water collector, 1 unit • 1.2 m of PVC pipe for water separator • Plug-in angle adapter for the pressure sensor connection tube, 1 unit • tube (green), 1 unit • information Sheet 	Ordinary	1y
AS-50060210	Kit manutenzione straordinaria Hybrid 1,2,5 The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Extraordinary	4.000h/4y