












MGF HYBRID 1S

Cod. AS-075-EX1

Semi-wet 0.75 Hp suction pump, maximum flow rate 1.100 l /min, underpressure 120 mbar. The high reliability of the centrifugal separation system guarantees correct operation of the suction pump for several years. The pump impellers are made of aluminum and guarantee maximum reliability over time. The HYBRID 1S model is also available with amalgam separator (code AS-075-EX-AS).

-  Maximum simultaneous use: 1
-  Dental Chairs: 2

								
Air capacity		Motor	Voltage Hz	Noise Level	Duty Cycle	max Oper. Head	Size	net Weight
m³/min	l/min	kW	230V 50Hz	db(A)	100 %	mbar	mm	Kg
0.0011	1.1	0.55		63		120/140	530x320x350	15

Maintenance kits

Kit.	Description	Type	Hours
AS-50060240	HYBRID 1, HYBRID 2 annual maintenance kit Comprehends: <ul style="list-style-type: none"> • Water collector - AS-50060214, 1 quantity • Non-return valve, water separator - AS-50060220, 1 quantity • 1.2 m of PVC pipe for water separation • Information Sheet 	Ordinary	1y
AS-50060210	Kit manutenzione straordinaria Hybrid 1,2,5 The extraordinary maintenance kit includes: liquid separator impeller, non-return valve, 15 mm fitting (with O-ring), clip and information sheet.	Ordinary	4.000h/4y